

CRF1000L DCT AFRICA TWIN

Key Information

Category (ies)	
Price	R208 500
Product Name	Africa Twin

General

Warranty	2yr
Service intervals	12000km
0 -- 100 km/h (sec)	

Dimensions and Weights

Claimed KERB weight (kg)	242
Length (mm)	2,335
Width (mm)	930
Height (mm)	1,475
Seat height (mm)	870/850mm (STD position / Low position)
Rake/trail (°/ mm)	
WheelBase (mm)	1,575mm

Drive

Drive	O-ring sealed chain
Front suspension	
Rear suspension	

Engine

Tank capacity (l)	18.8 litres
Starter	
Fuel system	
Engine configuration	Liquid-cooled 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam
Cylinders	2
Valves Per cylinder	4 Valves per Cylinder
Capacity (cc)	998cm ³
Power (KW)	70 @ 7,500rpm
Torque (NM)	98 @ 6,000rpm
Gearbox	6-Speed DCT

Safety

Brakes	310mm dual wave floating hydraulic disc with aluminium hub and radial fit 4-piston calipers (ABS*) and sintered metal pads. Rear - 256mm wave disc with 1 piston caliper and sintered metal pads. Also Lever-Lock Type Parking Brake System on DCT model with additional slide type 1-piston caliper. (ABS and Honda Selectrable Torque Control System)
--------	---

Styling

Frame material	Steel semi-double cradle type with high-tensile strength steel rear subframe
----------------	--

Wheels

Tyres (f)	90/90-R21 tube type
Tyres (r)	150/70-R18 tube type
Wheels	Front: 21 x 2.15 wire spoke with aluminium rim. Rear: 19 x MT4.00 wire spoke with aluminium rim